

iFocus



Features

- 7" TFT-LCD Touch Screen
- 800 x 600 (H x V)
- Rechargeable Lithium Ion Polymer battery
- IP or Analog cameras
- 30+ PTZ Protocols
- Supports ONVIF connection or Browser connection to

camera. Compatible with Impath, Mobotix, Speco, ACTi, Axis

Panasonic, Pelco and many others!

- 1 POE Port supplying up to 24W of power
- Built in LED lamp

Connections





Impath Networks Canada Corporation | 102 Chain Lake Drive, Unit 1K, Halifax, NS Canada B3S 1A7 | T: 902-468-1010 | F: 902-468-1044 | impathnetworks.com Copyright 2013 Impath Networks Canada Corporation. Impath is a registered trademark of Impath Networks Canada Corporation. TeleVue, ClientVue and i-Volution are trademarks of Impath Networks Canada Corporation All other trademarks are those of their respective owners. Printed in Canada – 02/13. Specifications subject to change without notice or obligation.

Specifications

MODEL	iFocus
Display	7 inch Capacitive touch screen
Operating System	Android OS
Network Port	10/100M auto adjust, RJ45
WIFI	Built in WIFI, up to 150M
IP Camera Type	ONVIF, ACTi, HIKVision, Samsung, Mobotix, Speco, Honeywell etc.
Video Level Test	1 channel BNC input & 1 channel Output, NTSC
Video Level Meter	PEAK video signal level, SYNC signal level and color burst level
Zoom	Supports IP and Analog camera image zoom
Recording	Image snapshots, record, save and view playback
HDMI Output	1 channel HDMI output supporting 1920 * 1080
12V/2A Power	12V DC power output for analog or IP camera
USB Power	5V, 2A output for charging mobile devices
POE Power	48V PoE power output, Max of 24W
Audio Test	1 channel audio signal input/output
PTZ Control	Supports RS232/RS485 control, Baud Rate Range 600-115200bps
Video Signal Generate	Output one channel NTSC/PAL color bar video signal
UTP Cable Tester	Test UTP cable connection status and display on screen
Data Monitor	Captures and analyzes the command data from controlling device
Digital Multi-meter (Instructed)	AC/DC Voltage, AC/DC current, Resistance, Capicitance, Data Hold Relative measurement, Continuity Testing (Optional)
Cable Scan	Search the cable by the audio system
PoE/PSE Voltage Test	Measurement POE switch or PSE power supply voltage and cable connection
Backup Mode	USB Device and Network
Network Test	IP address scan, link scan, ping test, auto search for IP devices
Built-In Apps	Browser, Photo View and Video Playback
Warranty	1 year
Accessories	Lanyard and wrist strap
Internal Storage	Micro SD compatible
USB	Single Input
External Power	12V DC, 2A
Battery	Built-In 7.4V Lithium polymer battery, 6500mAH
Rechargeable	7~8 hours for full change / Approx 16 hours working time
Auto Off	1-30 minutes
Working Temp	-10C~50C
Working Humidity	30%~90%RH
Dimensions	231mm×172mm×52mm (W×D×H)
Weight	1.26KG